

# I.D.

# EVO

# PRO SERIES

DRYCLEANING MACHINE



200 - 300 - 350 - 450





# EVO PRO SERIES

## 200 - 300 - 350 - 450

Drycleaning division

MODELLO Capacità per carica	MODELE Capacité par cycle	U.M. kg	2000 8	3000 10	3500 15	4500 19	MODEL Load capacity	U.M. lb	2000 18	3000 22	3500 33	4500 42
Tamburo: Diametro Profondità Volume Velocità di lavaggio Velocità di centrifuga	Tambour: Diamètre Profondeur Volume Vitesse de lavage Vitesse 1 d'essorage	mm mm dm <sup>3</sup> g/l' g/l'	710 410 160 45 500	710 530 210 45 500	850 530 300 40 500	900 565 360 40 450	Drum: Diameter Depth Volume Wash speed Extract speed 1	in in cu.ft. rpm rpm	28.0 16.1 5.7 45 500	28,0 20.9 7.8 45 500	33.5 20.9 10.5 40 500	35.4 22.2 12.9 40 450
Misure di ingombro: Larghezza Profondità Altezza Peso	Dimensions: Largeur Profondeur Hauteur Poids	mm mm mm kg	1550 1300 1950 950	1550 1300 1950 1200	1790 1450 1980 1420	1790 1450 1980 1650	Overall dimensions: Width Depth Height Weight	in in in lb	61.0 51.2 76.8 2090	61.0 51.2 76.8 2640	70.5 57.1 78.0 3124	70.5 57.1 78.0 3630
Serbatoi: 1° serbatoio 2° serbatoio 3° serbatoio	Réservoirs: 1° Réservoir 2° Réservoir 3° Réservoir	lt lt lt	85 85 135	85 85 135	105 105 145	120 120 160	Tanks: 1st Tank 2nd Tank 3rd Tank	US gals gals gals	22.5 22.5 35.7	22.5 22.5 35.7	27.7 27.7 38.3	31.7 31.7 42.3
Capacità filtri: Superficie filtrante Filtro decolorante Filtro ecologico	Capacité filtres: Filtre Nylon Filtre decolorante Filtre ecologique	m <sup>3</sup> N° lt	1,8 1 30	6 1 30	6,5 1 50	7 1 50	Filter capacity Filter surface Decolorating filter Ecological type	sq.ft. No. US gals	22 1 7.9	22 1 7.9	45 1 13.2	45 1 13.2
Distillatore	Distillateur	lt	125	135	205	225	Still	US gals	33.0	35.6	54.1	59.4
Dati di installazione:	Données d'installation:						Installation data:					
Ingresso acqua Pressione min. acqua Ingresso vapore Pressione max. vapore Potenza Impiegata Versione vapore Versione elettrica	Entrée eau Pression eau Entrée vapeur Pression vapeur Puissance employée Version vapeur Version électrique	Ø bar Ø bar kw kw	½" 1,5 ½" 4,5 4.2 13.8	½" 1,5 ½" 4,5 4.2 13.8	½" 1,5 ½" 4,5 4.8 16	½" 1,5 ½" 4,5 5.2 16.7	Water inlet Min. water pressure Steam supply Max. steam pressure Installed power Steam model Electric model	Ø psi Ø psi kw kw	½" 21.5 ½" 64 4.2 13.8	½" 21.5 ½" 64 4.2 13.8	½" 21.5 ½" 64 4.8 16	½" 21.5 ½" 64 5.2 16.7
Motori: Lavaggio Ventilatore Pompa Filtro Gruppo frigorifero	Moteurs: Lavage Ventilateur Pompe Filtre Groupe frigo	kw kw kw kw kw	1,1 0,75 0,55 0,35 2,2	1,1 0,75 0,55 0,35 2,2	1,1 0,75 0,55 0,35 2,6	1,1 1,1 0,55 0,35 2,6	Motors: Wash speed Fan Pump Filter Refrigerating unit	kw kw kw kw kw	1.1 0.75 0.55 0.35 2.2	1.1 0.75 0.55 0.35 2.2	1.1 0.75 0.55 0.35 2.6	1.1 1.1 0.55 0.35 2.6

Descrizioni, dati, misure, colori non sono impegnativi e possono variare senza alcun preavviso  
 Descriptions, weights, measurements, pictures and colours are not binding.  
 Descriptions, poids, mesures, figures et couleurs sont donnés sans engagement de notre part.

**ITALIAN DRYCLEANING S.R.L.**  
 Via XXV Aprile, 20  
 52100 Arezzo (AR) - Italy

Tel. ++39 075 8521264  
 Fax. ++39 075 8520717  
 Mail: sales@italiandrycleaning.it  
 Web: www.italiandrycleaning.it